300 V CAT III



A Single Instrument for Locating All Your Metal Conductors



of faults in electrical cables,

telecommunication cables and pipes.

Locate hidden cables

For your housing maintenance, renovation and improvement work, the LOCAT-N C.A 6881 detects electrical power cables and telecommunication cables, metal pipes and even anomalies on your lines.

Comprising a C.A 6881E transmitter and a C.A 6881R receiver, the LOCAT-N C.A 6681 is **simple to use** on both current-carrying and non-current-carrying mains circuits. Its digital technology overcomes interference and disturbance signals to provide precise location details. The receiver displays the value of the signal measured, which is also shown on the bar chart or in the form of acoustic signals

whose amplitudes vary in proportion to the signal distance. This makes it **very simple to follow electrical cables through walls** or detect buried pipes in gardens.

To guide you and **simplify your work**, the receiver can quickly identify the circuit-breaker or fuses corresponding to the socket to which the transmitter is connected. It can be used to detect short-circuits or cuts on existing installations. For example, it is possible to detect faults in under-floor heating pipes. These ergonomic instruments are **lightweight** and delivered complete with practical accessories for direct measurements on screw-in or bayonet lamp sockets or on mains power sockets.



Applications






Location and tracking of lines and sockets

2 measurement methods according to the installation configuration



Identification of the network voltage and search interruptions in the circuit



Identification of fusesConnect the transmitter to a power socket for simple identification of

the corresponding fuse




Location of line interruptionsQuick, simple detection of interruptions in your walls



Quick identification of the cause of the problem




Detection of the pinched or obstructed part in a non-metallic pipe




Tracking of buried circuits



Fault detection in under-floor heating systems



Detection of metal heating ducts



Detection of metal water pipes

Technical specifications

C.A 6681E transmitter		
Screen	LCD screen with display of functions and bargraph	
Output signal frequency	125 kHz	
External voltage measurement range	12 to 600 VAC/DC	
Functions	Digital coding of signals for easy signal identification, selection of transmission signal code, torch function	
Power supply	9 V battery	
Dimensions	190 x 89 x 42.5 mm	
Weight	420 g with battery	
Electrical safety	300 V CAT III	

C.A 6681R receiver		
Screen		Backlit LCD with display of functions and bargraph, transmission code, receiver and transmitter battery-charge status
Detection depth	Single-pole application Two-pole application Simple looping line	0 to 2 m 0 to 0.5 m Up to 2.5 m
Identification of mains voltage		Approximately 0 to 0.4 m
Functions		Automatic shutdown, automatic or manual adjustment of reception sensitivity, torch function
Power supply		6 x 1.5 V AAA batteries
Dimensions		241.5 x 78 x 38.5 mm
Weight		360 g with batteries

To order



C.A 6681 LOCAT-N **P01141626**

C.A 6681E transmitter and C.A 6681R receiver delivered in a hard case with 1 set of red/black 4 mm isolated banana leads (straight male / elbowed male), 1 set of 2 crocodile clips, 1 stake for earthing, 1 x 9 V battery, 6 x 1.5 V AAA batteries, 1 measurement adapter for B22 socket (bayonet), 1 adapter for E14 socket (screw-in), 1 mains socket adapter and 1 operating manual in 5 languages.

For information and ordering

OI

北京海洋兴业科技股份有限公司(证券代码: 839145)

北京市西三旗东黄平路19号龙旗广场4号楼(E座)906室 邮编: 100096

电话: 010-62176775 62178811 62176785 企业QQ: 800057747 维修QQ: 508005118

企业官网: www.hyxyyq.com

传真: 010-62176619

邮箱: market@oitek.com.cn

购线网: www.gooxian.com



扫描二维码关注我们 查找微信公众号:海洋仪器